

2-KOMPONENT ANLEGG

Produktnummer: 20017

WIWA Duomix 85 to-komponent pumpe

WIWA FLEXIMIX 2 HERKULES GX

Maximum capacity for highest demands, day by day

The new electronically controlled FLEXIMIX-II-HERKULES GX plural component range was designed and constructed to fulfill highest requirements. Enormous area output, high layer thicknesses and the simultaneous use of several spray guns or extremely long hose lines make this system particularly suitable for large area and thick-film coating.

Even materials, that could previously not or only conditionally be sprayed, can now be applied with the FLEXIMIX-II-HERKULES GX. Due to the high volumetric capacity the Herkules plural component range is ideally suited for manual and automatic coating systems. The extensive range of WIWA accessories enables optimal adaptation to any application. Special options are also possible.

Volumetric mixing ratios 0.5:1 to 17:1 (270) 0.5:1 to 17:1 (333GX)

Pressure ratio 24:1 to 88:1 (270) 37:1 to 75:1 (333GX)

Maximum operating pressure up to 497 bar (270) up to 487 bar (333GX)

Controllable components up to 4 (270 + 333GX)

Application areas

- Autom. coating plants and other applications with high performance requirements under extreme conditions
- Heavy corrosion protection
- Sound and fire protection
- Insulating coatings
- Industrial coatings
- Pipe and tank coatings

- Marine and offshore industri