



# POLYUREA OG PU SKUMANLEGG

---

Produktnummer: .

**WIWA DUOMIX SPF 280**

## WIWA DUOMIX SPF 280

---

**16:1/144ccm**

### Simplicity at its finest!

---

WIWA SPF spray rigs are designed for ease of use. Direct view of all gauges, simple software settings. Connect. Turn on. Spray. Job done.

### Technical data

---

Model	SPF 280
Pressure ratio	16:1
Output per cycle	144 ccm
Max. inbound air pressure	8 bar
Max. operating pressure	128 bar
Material fluid heater	6 kW
Max. heating capacity hose package	3.5 kW
Max. hose length	64 m
Voltage phases	230 - 400 V/3 P
Max. power requirement	9.5 kW

N - Normal steel galvanized, not stainless, R - stainless, RS - Stainless steel, rust and acid resistant.

B - On container, D - on tripod, F - on chassis, G - on rack, GZ - With feed funnel, W - on wall mount.

## **Application areas**

---

- Bridge waterproofing
- Pools
- Natural swimming pools
- Pond linings
- Fish farms
- Drinking water reservoirs
- Catch basins(also chemical resistant)
- sewage treatment plants
- Foundations
- Industrial floors and walls
- Concrete and building restoration
- Hangar floors
- Roof insulation and waterproofing
- Insulation of cavities
- Parking decks
- Sound insulation of track beds
- Railcar construction
- Ship and ferry decks
- Container construction
- Pipes and pipelines
- Wind energy
- Submarines
- Buoys

## **Material**

---

- Polyurea and polyurethane foams

## **DOWNLOAD BROCHURE**

---